


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS656W
Parker Part No:	938258Q
OEM:	Hydac
OEM Part No:	0060R005BN4HC

Product Dimensions

A (mm)	51.5	(inch)	2.03
C (mm)	22.2	(inch)	0.87
D (mm)	51.5	(inch)	2.03
E (mm)	103.0	(inch)	4.06
G (mm)	24.0	(inch)	0.94
H (mm)	10.5	(inch)	0.41



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon
Bottom Endcap:	Glass reinforced nylon
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.41 bar @ 30 l/min
Tested to ISO3968 @ 32 cSt	5.95 psi @ 6.60 gpm
Efficiency:	>Beta 200 @ 6 microns & greater >Beta 1000 @ 7 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	7.2 gram @ 4 bar terminal pressure drop 7.2 gram @ 58 psi terminal pressure drop